

Product Data Sheet

☎ 1-888-452-HANA (4262) ✉ info@hanawireless.com

✉ 9465 Southampton Pl, Boca Raton, FL 33434, USA



Model: HW2-N14-V

14x12x7 Inch Weatherproof Enclosure with Slotted Mounting Plate, Vent System



Features

- Molded Fiberglass Reinforced Polyester (FRP)
- Stainless steel quick-release latches with padlock hasps
- NEMA Type 3R, 3RX / IP24 rated, fully gasketed lid
- Integral mounting flange, mast mounting option
- Aluminum mounting plate, ventilation system, patented (US8014157) slotted accessory mounting design

Applications

- Remote wireless LAN Wi-Fi equipment installations
- Indoor and outdoor installations
- Rapid deployment and hotspot installations
- Harsh and corrosive environments
- Protection of equipment from theft and damage

Specifications

Material	FRP
Color	Tool Gray – RAL 7035
Voltage Vac	N/A
Heater F° (C°)	N/A
Heat Temperature ON/OFF F° (C°)	N/A
Fan Power Watt	N/A
Fan Temperature ON/OFF F° (C°)	N/A
Mounting Plate Dimensions in (mm)	12.7 (322) x 10.8 (274) x 0.1 (2.5)
Mounting Plate Material	Anodized Aluminum
Weight lb (kg)	10.6 (4.8)
Outside Dimensions, Max in (mm)	15.5 (393) x 13.5 (342) x 8.7 (220)
Inside Dimensions in (mm)	13.5 (343) x 11.5 (292) x 5.8 (147)
Flame Rating	UL 94-5V
RoHS	Compliant
Environmental Rating NEMA - IP	3R, 3RX - 24
Cable Feed	1/2in Conduit Connector

Package Specifications

Package Quantity	1 per Carton
Length in (mm)	16.0 (406)
Width in (mm)	16.0 (406)
Depth in (mm)	16.0 (406)
Weight lb (kg)	11.1 (5.0)

Wireless That Works